甲基丙烯酸羟丙酯(HPMA) 2-HYDROXY PROPYL METHACRYLATE

CAS NO.:	分子式/Molecular Structure:	
27813-02-1	CH ₂ =C(CH ₃)COOCH ₂ CH(OH)CH ₃	

项 目 Items	规格 Specification	测试方法 Test Method
含量 Purity	97Min	G-C
色度 Colour	15Max	DIN EN 1557
水分 Water content	0.15Max	ASTM E203
游离酸 Acid content(As MAA)	0.2Max	DIN EN ISO2114
阻聚剂 Inhibitor	180-220	SPECTROPHOTOGR APHY

应用/Application:

主要用于生产涂料、合成汽车面漆和底漆用的树脂。还可以用于树脂、密封胶及其他胶黏剂等。

Mainly used in the production of coatings. It copolymerizes with monomers such as styrene, methyl methacrylate, butyl acrylate and meth-acrylic acid and etc. To produce coatings and primers for auto applications. Also used in the production of resin, porous metal parts, sealants and caulks and other adhesives formulations.

包装/Packing:

200kg 塑料桶, 200kg 钢桶, IBC桶, 集装罐 200KG HDPE DRUM, 200KG STEEL DRUM, IBC DRUM, ISOTANK